



WMS

Spec Fixture



IP67

Watt	NO	Length
6W	PP-TPL233	280
10W	PP-TPL333	380
12W	PP-TPL398	445
20W	PP-TPL633	680
28W	PP-TPL833	880
30W	PP-TPL933	980
40W	PP-TPL1203	1250
All type	IP67	W=30, H=52

Same price for 24V AC/DC - 230 V AC.



IP69K

Watt	NO	Length
20W	PP-IP69X2	600
36W	PP-IP69X4	1200
45W	PP-IP69X5	1500
All type	IP69K	Ø 75

Standart with 1 + 2 cable intering.



IP66 / IP67

PP-13-49W	PC+304 and mont iron IP66	1500
PP-23-15W	PC+ 304	600
PP-24-32W	PC+ 304	1200
PP-25-49W	PC+ 304 IP66	1500
PP-31-15W	PC+all 316	600
PP-32-32W	PC+all 316	1200
PP-33-49W	IP67	1500



NO	W	Dim	Length
PP-PZ 600	10	T8	600
PP-PZ 1200	22	T8	1200
PP-PZ 1500	44	T8	1500

PP-PZ 60024 10 T8 600

Input voltage: 12 - 276 V AC/DC

PP-TL5 600	10	T5	600
PP-TL5 1200	18	T5	1200
PP-TL5 1500	25	T5	1500

IP68-2, IK-10



NO	W	Material	IP68-2/IK10
PPRI1X18	18	304 /316	X
PPRI1X36	36	304 /316	X
PPRI1X58	58	304 /316	X
PPRI2X18	2X18	304 /316	X
PPRI2X36	2X36	304 /316	X
PPRI2X58	2X58	304 /316	X
PPRI1X14T5	1X14	304 /316	X
PPRI1X28T5	1X28	304 /316	X
PPRI1X35T5	1X35	304 /316	X
PPRI1X39T5	1X39	304 /316	X
PPRI1X54T5	1X54	304 /316	X
PPRI1X80T5	1X80	304 /316	X
PPRI2X14T5	2X14	304 /316	X
PPRI2X21T5	2X21	304 /316	X
PPRI2X39T5	2X39	304 /316	X
PPRI2X54T5	2X54	304 /316	X
PPRI1X18 HF	1X18	304 /316	X
PPRI1X36HF	1X36	304 /316	X
PPRI1X58HF	1X58	304 /316	X
PPRI2X18HF	2X18	304 /316	X
PPRI2X36HF	2X36	304 /316	X
PPRI2X58HF	2X58	304 /316	X

HF are fixture for 85C and with 2 cable intering.

Mobile: +45 40987624

Order / Contact: info@worldmarinesupply.com